

Portable Welding Fume Filter *SRF T-2 / SRF T-4*




Portable welding fume filter SRF T-2



SRF T-4, a mobile device for two extraction points or for connection to pipe systems

Application Range

- » For the direct extraction at the welding torch
- » Outside work, assembly or construction sites
- » Non-alloy steels and steel with low alloy content



Test certificates (optional)

W3



SRF T-2

Gefahrstoffgeprüft
Schweißrauch-
abscheideklasse W3

Special Versions

- » Exhaust air connection
- » Special voltage
- » IFA Test Certificates W3 (SRF T-2) for high-alloy metals
- » Activated carbon filter
- » Custom paint finish



SRF T-2, direct extraction from one welding torch

Accessories



Slotted nozzle. Order Number 94.741



Cone shaped nozzle. Order Number 94.740

Special Features

- » Powerful suction turbine
- » Integrated compressed air cleaning nozzle
- » Cleanable long life cartridge filters (Dust classification M)
- » Direct extraction of welding torches or nozzles

Your Benefits

- » High performance direct extraction of welding torches or nozzles
- » Portable units that can be used in any location
- » Compact and functional design
- » Low operating costs with cleanable long life cartridge filters

Data dependent on equipment type

Technical Data

Welding fume filter model SRF		T-2*	T-4
Max. Airflow	m ³ /h	200	400
Intake diameter	mm	50	2 x 50
Max. negative pressure	Pa	19.000	19.000
Voltage	V	230	230
Motor	kW	1.1	2.2
Filter surface	m ²	0,8	1,6
Dimensions (L/W/H)	mm	390 x 210 x 500	490 x 400 x 560
Weight	kg	15	27
Sound emission	dB(A)	66	78
Order Number		55.101	55.102

* available in W3-tested Version